

WHAT IS CLAIMED IS:

1. A method of creating a template, said method comprising:  
disposing a diamond-like composition on a surface of said template having properties sufficient to be substantially transmissive of a predetermined wavelength and provide said surface.
2. The method as recited in claim 1 wherein disposing further includes disposing said diamond-like composition from a set of diamond-like compositions consisting of including diamond-like carbon (DLC) and diamond-like nano-composites.
3. The method as recited in claim 2 wherein said nano-composites includes DYLYN<sup>®</sup>.
4. The method as recited in claim 1 wherein said predetermined wavelength includes UV light.
5. The method as recited in claim 1 where disposing further includes patterning said diamond-like composition.
6. The method as recited in claim 1 further including doping said diamond-like composition with electrically conductive elements.
7. The method as recited in claim 1 further including depositing an electrically conductive layer upon

said substrate before depositing said diamond-like composition.

8. The method as recited in claim 1 further including depositing an electrically conductive layer upon said substrate before depositing said diamond-like composition and patterning said diamond-like composition to selectively expose regions of said electrically conductive layer.

9. The method as recited in claim 1 further including forming said template from a fused-silica.

10. A method of creating a template, said method comprising:

disposing a diamond-like composition on a surface of said template having properties sufficient to be substantially transmissive of a predetermined wavelength and provide said surface with a predetermined surface energy; and

patterning said diamond-like composition to includes a plurality of protrusions and recesses.

11. The method as recited in claim 10 wherein disposing further includes disposing said diamond-like composition from a set of diamond-like compositions consisting of including diamond-like carbon (DLC) and DYLYN®.

12. The method as recited in claim 10 wherein said predetermined wavelength includes UV light.

13. The method as recited in claim 10 further including doping said diamond-like composition with electrically conductive elements.

15. The method as recited in claim 10 further including depositing an electrically conductive layer upon said substrate before depositing said diamond-like composition.

16. The method as recited in claim 10 wherein patterning further includes said diamond-like composition to selectively expose regions of said electrically conductive layer.

17. A method of creating a template, said method comprising:

forming an electrically conductive layer on said template having properties to be substantially transmissive of a predetermined wavelength;

disposing a diamond-like composition on a surface of said template having properties sufficient to be substantially transmissive of said predetermined wavelength and provide said surface with a predetermined surface energy; and

patterning said diamond-like composition to include a plurality of protrusions and recesses and selective expose portions of said electrically conductive layer.

18. The method as recited in claim 17 wherein disposing further includes disposing said diamond-like

composition from a set of diamond-like compositions consisting of including diamond-like carbon (DLC) and DYLYN<sup>®</sup>.

19. The method as recited in claim 17 wherein said predetermined wavelength includes UV light.

20. The method as recited in claim 17 further including depositing an electrically conductive layer upon said substrate before depositing said diamond-like composition.

21. A template for use in imprint lithography, said template comprising:

a body;

a diamond-like composition disposed on said body, with said diamond-like composition being substantially transparent to a predetermined wavelength of light and having a predetermined surface energy associated therewith.

22. The template as recited in claim 21 wherein said diamond-like composition is electrically conductive.

23. The template as recited in claim 21 wherein said diamond-like composition includes a plurality of protrusions and recesses.

24. The template as recited in claim 21 further including an electrically conductive layer position between said body and said diamond-like composition.

25. The template as recited in claim 23 wherein said diamond-like composition includes a plurality of protrusions and recesses, with said electrically conductive layer being exposed in said recesses.

26. The template as recited in claim 23 wherein said electrically conductive layer is formed from Indium Tin Oxide.